

| Transaction | Function Supported by Transaction²⁵ |
|---|---|
| Resupply | Request from a Long Term or Post-Acute Care (LTPAC) organization to a pharmacy to send an additional supply of medication for an existing order. |
| Verify | Response to a pharmacy or prescriber indicating that a transaction requesting a return receipt has been received. |
| CancelRx and CancelRxResponse | Request from the prescriber to the pharmacy to inactivate a previously sent prescription. Response is sent from the pharmacy to the prescriber to acknowledge a cancel request. |
| RxFill | Indicates the dispensing or activity status. It is the notification from one entity to another conveying the status of dispensing activities or other clinical activities. |
| DrugAdministration | Communicates drug administration events from a prescriber/care facility to the pharmacy or other entity. It is a notification from a prescriber/care facility to a pharmacy or other entity that a drug administration event has occurred. |
| NewRxRequest | Request from a pharmacy to a prescriber for a new prescription for a patient. If approved, a NewRx transaction would be sent. |
| NewRx | New prescription is sent from the prescriber to the pharmacy electronically so it can be dispensed to a patient. |
| NewRxResponseDenied | Denied response to a previously sent NewRxRequest. |
| RxTransferInitiationRequest (previously named RxTransferRequest in NCPDP SCRIPT standard version 2017071) | Used when the destination pharmacy is asking for a transfer of one or more prescriptions for a specific patient from the source pharmacy. |
| RxTransfer (previously named RxTransferResponse NCPDP SCRIPT standard version 2017071) | In the solicited model, it is the response to the RxTransferInitiationRequest which includes the prescription(s) being transferred from the source pharmacy to the destination pharmacy or a rejection of the transfer request. In the unsolicited model, it is a push of the prescription(s) being transferred from the source pharmacy to the destination pharmacy. |
| RxTransferConfirm | Used by the destination pharmacy to confirm the transfer prescription has been received and the transfer is complete. |
| RxFillIndicatorChange | Sent to the receiver to indicate the sender is changing the types of RxFill responses that were previously requested. The sender may modify the fill status notification of transactions previously selected or cancel future RxFill transactions. |
| Recertification | Notification on behalf of a reviewing provider to a pharmacy recertifying the continued administration of a medication order. Used in LTPAC only. |
| REMSInitiationRequest and REMSInitiationResponse | Request to the REMS Administrator for the information required to submit a REMS request (REMSRequest) for a specified patient and drug. Response is from the REMS Administrator with the information required to submit a REMS request (REMSRequest) for a specified patient and drug. |